



EDENOL® DOZ

Plasticizer

Description

EDENOL® DOZ is a di-(2-ethylhexyl)-azelate.

General Appearance

Slightly yellow, liquid

Specified Data

Parameter	Value	Test Method*
Acid value (mg KOH/g)	0 - 1.0	AOCS Te 1a-64T DIN EN ISO 2114
Color Gardner	0 - 1.0	DIN ISO 4630
Density (20 °C)	0.913 - 0.919	ASTM D1045 DIN 51757
Hydroxyl value (mg KOH/g)	0 - 2.2	AOCS Cd 1360 DIN 53240
Moisture (%)	0 - 0.1	DIN 51777
Refractive index (20 °C)	1.445 - 1.451	DIN51423

* Test method: ASTM, AOCS (USA) | DIN (Europe)

Properties and Applications

EDENOL® DOZ is one of the best low-temperature plasticizers commercially available. The outstanding compatibility of EDENOL® DOZ enables it to be used as the sole plasticizer for applications demanding best low-temperature performance, while its relatively low volatility enables compounds to maintain their properties over extended periods of time. EDENOL® DOZ exhibits excellent resistance to extraction by water, oil and soapy water. Vinyl film, sheeting and coated fabrics prepared with EDENOL® DOZ show excellent surface properties and softness. These vinyls also exhibit excellent long-term aging properties and heat stability. In most applications, DOZ can replace 1:1 dioctyl sebacate (DOS) without loss in performance.

EDENOL® DOZ is suitable for PVC, NBR, NBR/PVC, HNBR, CR, CM and CSM.



Recommended Dosage

5 - 45 phr

Certifications

EDENOL® DOZ complies with indirect food contact directives. Further information is available upon request.

Additional Properties

Parameter	Value	Test Method*
Pour point (°C)	< -67	ASTM D97 DIN ISO 3016

* Test method: ASTM (USA) | DIN (Europe)

Health and Safety Information

Please review our Safety Data Sheet for best practices when using this material.

Packaging Sizes

IBC tote, liquid
Drum, liquid

Storage and Handling

It is recommended to store EDENOL® DOZ at room temperature and to protect the product against the effects of heat and frost. If stored in original sealed containers, EDENOL® DOZ should be stable for at least 24 months from the date of manufacture.

Emery Oleochemicals GmbH
T | +49 211 5611 2000
E | gp.europe@emeryoleo.com

Emery Oleochemicals LLC
T | +1 513 762 2500
E | gp.americas@emeryoleo.com

Emery Oleochemicals (M) Sdn Bhd
T | +603 3326 8686
E | gp.asia@emeryoleo.com

Disclaimer: The content in this document is provided on an "as is" and "as available" basis purely for informational purposes and, unless and to the extent specifically agreed otherwise for a sales transaction, does not constitute any warranty, whether express, implied or statutory, including but not limited to warranties or guarantees of merchantability, fitness or suitability for a particular purpose nor any representations of a binding nature. EMERY OLEOCHEMICALS EXPRESSLY DISCLAIMS ANY RESPONSIBILITY FOR THE SUITABILITY OF THE PRODUCTS FOR ANY SPECIFIC OR PARTICULAR PURPOSES INTENDED BY THE USER. Suggestions for the use and application of the products and guide formulations are for informational purposes only and you are advised to carry out any necessary steps to test the suitability of the products for your intended processes and purposes. You are solely responsible for compliance with all applicable laws and regulations in use of the products including any third party intellectual property rights and shall bear all liability or risk arising from use of the products. All indications marked with a TM or ® symbol are trademarks belonging to legal entities within the Emery Oleochemicals group of companies.